



**T. J. SNOW**

# Rocker Arm Spot Welder

## Features

- Solid copper arms drilled at 30 or 90 degree angles to accommodate water-cooled electrode holders
- 8-point heat selector switch on a stacked core transformer
- 3 circuit water manifolds for input and output water cooling
- 5" x 4" stroke double acting air cylinder
- 4-way solenoid operated air valve, air line filter, pressure regulator
- Single-stage shrouded foot switch
- Fork lift pockets for safe & easy handling

## Specs

- 30, 50, 75, 100, 150 kVA models
- Available in 208, 220, 440 & 550 V
- Single Phase / AC / 60 Hz



kVA	RWMA Size	Volts	Throat Depth	Force	Length	Width	Height	Copper Arms	Weight
30	2	208, 220, 440, 550	18"	1,380 lbs	54"	12"	49"	2.5"	1,016 lbs
			24"	1,075 lbs	60"				1,035 lbs
			30"	875 lbs	66"				1,098 lbs
			36"	743 lbs	72"				1,117 lbs
50	2		18"	1,380 lbs	54"	12"	49"	2.5"	1,070 lbs
			24"	1,075 lbs	60"				1,089 lbs
			30"	875 lbs	66"				1,153 lbs
			36"	743 lbs	72"				1,172 lbs
75	3		18"	2,180 lbs	54"	12"	49"	2.5"	1,125 lbs
			24"	1,700 lbs	60"				1,144 lbs
			30"	1,390 lbs	66"				1,207 lbs
			36"	1,175 lbs	72"				1,226 lbs
100	3		18"	2,860 lbs	84"	14.5"	54"	3"	1,776 lbs
			24"	2,150 lbs	90"				1,788 lbs
			36"	1,430 lbs	96"				1,800 lbs
150	3		18"	2,860 lbs	84"	14.5"	54"	3"	1,851 lbs
		24"	2,150 lbs	90"	1,863 lbs				
		36"	1,430 lbs	96"	1,875 lbs				

**EMAIL:** [welders@tjsnow.com](mailto:welders@tjsnow.com) | [tjsnow.com](http://tjsnow.com)  
120 Nowlin Lane | Chattanooga, TN 37421

CALL TO GET A QUOTE  
**423.894.6234**